

# NISSAN FORKLIFT TRUCKS, DIESEL DX-15 QD32 (2007 AND AFTER)



## ENGINE Nissan QD32

USE Normal	CLIMATE Mediterranean
---------------	--------------------------

PRODUCT RECOMMENDATION 1 <b>Dieselfleet CD+ 15W-40</b>	PRODUCT RECOMMENDATION 2 <b>Multifleet SHPD 15W-40</b>	PRODUCT RECOMMENDATION 3 <b>Multifleet SCD 30</b>
---	---	--

*Check every 10 hours, change every 500 hours*

USE Normal	CLIMATE Moderate
---------------	---------------------

PRODUCT RECOMMENDATION 1 <b>Kroontrak MTH 10W-30</b>	PRODUCT RECOMMENDATION 2 <b>Synfleet SHPD 10W-40</b>	PRODUCT RECOMMENDATION 3 <b>Multifleet SHPD 10W-40</b>
---	---	---

*Check every 10 hours, change every 500 hours*

## DIFFERENTIAL FRONT

USE Normal	CLIMATE Mediterranean
---------------	--------------------------

PRODUCT RECOMMENDATION 1 <b>Gearlube GL-5 85W-140</b>		
--	--	--

*Change every 12 months/ 2400 hours*

USE Normal	CLIMATE Cold
---------------	-----------------

PRODUCT RECOMMENDATION 1 <b>Gearlube GL-5 80W-90</b>	PRODUCT RECOMMENDATION 2 <b>Unigear HS GL-3/GL-5 80W-90</b>	
---	--	--

*Change every 12 months/ 2400 hours*

## TRANSMISSION AUTOMATIC

USE Normal	CLIMATE Moderate
---------------	---------------------

PRODUCT RECOMMENDATION 1 <b>ATF Dexron II-D</b>	PRODUCT RECOMMENDATION 2 <b>ATF-F (Ford)</b>	
--	---	--

*Change every 6 months/ 1200 hours*

## HYDRAULIC SYSTEM

USE Normal	CLIMATE Moderate
---------------	---------------------

PRODUCT RECOMMENDATION 1 <b>Perlus H 32</b>		
--	--	--

*Change every 12 months/ 2400 hours*

# NISSAN FORKLIFT TRUCKS, DIESEL DX-15 QD32 (2007 AND AFTER)



## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		
<i>Change every 12 months/ 2400 hours</i>		

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Grease EP 1</b>		
<i>Change every 3 months/ 600 hours</i>		

## GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	
<i>Change every 12 months/ 2400 hours</i>			

## COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*