## NISSAN FORKLIFT TRUCKS, ELECTRIC B01



DIFFERENTIAL		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 12 months/ 2400 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 12 months/ 2400 hours		

REDUCTION GEARS		
USE	CLIMATE	
Normal	Mediterranean	
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
Change every 12 months/ 2400 hours		
USE	CLIMATE	
Normal	Moderate	

		incaciato
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change avery 12 months/2400 hours		

Change every	12 months/	2400 hours
--------------	------------	------------

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Change every 6 months/ 1200 hours	

GREASE POINTS/NIPPLES CHASSIS	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Gear Grease EP 1	

## **NISSAN FORKLIFT TRUCKS, ELECTRIC B01**



GREASE POINTS/NIPPLES MAST + CHAIN GUIDE BAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

LIFT CHAINS		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 30		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Industrial Chain Spray		
	•	•
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
HDX 20W-20		

WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.