

# PEL-JOB WHEELED LOADERS EW50



**ENGINE** Perkins 104-22  
Capacity: 8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 250 hours*

**DIFFERENTIAL**  
Capacity: 9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 800 hours*

**TRANSFERBOX**  
Capacity: 1,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 800 hours*

# PEL-JOB WHEELED LOADERS EW50



## HYDRAULIC SYSTEM

Capacity: 106 liter, Capacity: 70 liter (Hydraulic tank)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 68</b>       |  |  |

*Change every 800 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 46</b>       |  |  |

*Change every 800 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 32</b>       |  |  |

*Change every 800 hours*

| USE               | CLIMATE  |
|-------------------|----------|
| Biodegradable oil | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Perlus Biosynth 46</b> |  |  |

*Change every 800 hours*

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
|--------------------------|---------------------------------|------------------------------|
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## COOLING SYSTEM

Capacity: 10 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |  |
|-------------------------------|--------------------------|--|
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |  |

# PEL-JOB WHEELED LOADERS EW50


**TRAVEL REDUCTION UNIT**

Capacity: 0,7 liter (each hub)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

## PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 800 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*