

| ENGINE Cummins QSL9<br>Capacity: 21 liter |                          |          |
|---|--------------------------|----------|
| USE                                       |                          | CLIMATE  |
| Normal                                    |                          | Moderate |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2 |          |
| Agrisynth LSP 10W-40                      | Armado Synth 10W-40      |          |
|   |                          |          |

Check every 10 hours, change every 500 hours/ 12 months

| FINAL REDUCTION<br>Capacity: 4 liter (each side) |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011                                     | Syngear TDL 75W-90       | Abacot MEP Synth 220     |

Change every 800 hours/ 12 months

| TRANSFERBOX<br>Capacity: 1,8 liter |                          |                          |
|------------------------------------|--------------------------|--------------------------|
| USE                                |                          | CLIMATE                  |
| Normal                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011                       | Syngear TDL 75W-90       | Abacot MEP Synth 220     |

Change every 800 hours/ 12 months

| TRANSMISSION/HYDRAULIC SYSTEM<br>Capacity: 80 liter (System) |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                                     |          |
| ATF Dexron II-D  |          |
| Change every 1200 hours/ 12 months                           |          |

| GREASE POINTS/NIPPLES GENERAL |                          |          |
|-------------------------------|--------------------------|----------|
| USE                           |                          | CLIMATE  |
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| Q5 MP Calcep Grease EP 2      | MP Lithep Grease EP 2    |          |



| COOLING SYSTEM<br>Capacity: 30 liter |                          |                          |
|--------------------------------------|--------------------------|--------------------------|
| USE                                  |                          | CLIMATE                  |
| Normal                               |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1             | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+                       | Coolant SP 12            | Coolant -38 Organic NF   |

Change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.