

POWERSCREEN MINING & QUARRYING EQUIPMENT CHIEFTAIN 1700S DEUTZ TCD2013 L04 2V (TIER 3)



ENGINE Deutz TDC2013 L04 2V
Capacity: 14 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Change every 250 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth LSP 10W-40

Change every 250 hours/ 12 months

FEEDER GEARBOX

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 150

PRODUCT RECOMMENDATION 2

Abacot MEP 150

Change every 2000 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 150

PRODUCT RECOMMENDATION 2

Abacot MEP 150

Change every 50 hours

HYDRAULIC SYSTEM

Capacity: 564 liter (Tank)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Perlus AF 100

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus AF 46

Change every 2000 hours

POWERSCREEN MINING & QUARRYING EQUIPMENT CHIEFTAIN 1700S DEUTZ TCD2013 L04 2V (TIER 3)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 13,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 24 months/ 3000 hours

SCREEN BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

TRACK GEARBOX

Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP 320		

VIBRATING GRID

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.