PRODUCT RECOMMENDATION

SHUTTLELIFT 5500 5540F CUMMINS QSB
(2008 AND AFTER)

ENGINE Cummins QSB3.3
Capacity: 10,9 liter, Filter capacity: 1,4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	

Check every 10 hours, change every 1 months/ 250 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL FRONT
Capacity: 23 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 3 months/ 500 hours, change every 6 months/ 1000 hours

HUB REDUCTIONS FRONT
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 3 months/ 500 hours, change every 6 months/ 1000 hours

TRANSMISSION MANUAL ITL 4/4

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF-F (Ford)		

Check every 10 hours, change every 6 months/ 1000 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SHUTTLELIFT 5500 5540F CUMMINS QSB
(2008 AND AFTER)

HYDRAULIC SYSTEM
Capacity: 89 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 10 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 50 hours

COOLING SYSTEM
Capacity: 21,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Coolant -38 Organic NF	**Coolant -26**

Check every 10 hours, change every 2000 hours/ 12 months

HOIST REDUCTION UNIT Tulsa
Capacity: 1,4-1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Change every 1000 hours/ 6 months

HOIST WINCH BRAKE Tulsa
Capacity: 0,2-0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SHUTTLELIFT 5500 5540F CUMMINS QSB
(2008 AND AFTER)

SWING REDUCTION UNIT Braden Capacity: 0,95 liter		
USE Normal		**CLIMATE** Moderate
PRODUCT RECOMMENDATION 1 **Abacot MEP 460**		
Change every 1000 hours/ 6 months		

SWING REDUCTION UNIT Tulsa		
USE Normal		**CLIMATE** Moderate
PRODUCT RECOMMENDATION 1 **Labora Grease**	**PRODUCT RECOMMENDATION 2** **Q5 MP Calcep Grease EP 2**	**PRODUCT RECOMMENDATION 3** **MP Lithep Grease EP 2**
Check every 3 months/ 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367