

# SKYJACK TELEHANDLERS VR-1044D

## CUMMINS QSB3.3 TIER 3 ( <- 87200037)



**ENGINE** Cummins QSB3.3 Tier 3  
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

*Check every 8 hours, change every 3 months/ 250 hours*

**DIFFERENTIAL FRONT**

Capacity: 14,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours/ 12 months*

**DIFFERENTIAL REAR**

Capacity: 17 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours/ 12 months*

**HUB REDUCTIONS REAR**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours/ 12 months*

# SKYJACK TELEHANDLERS VR-1044D

## CUMMINS QSB3.3 TIER 3 ( <- 87200037)



**TRANSMISSION** Dana T12000 3/3  
Capacity: 12,9 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30**

*Change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus**

*Change every 1000 hours/ 12 months*

### HYDRAULIC SYSTEM

Capacity: 151 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32**

*Check every 8 hours, change every 12 months/ 1000 hours*

### COOLING SYSTEM

Capacity: 15,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

*Check every 8 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.