

## SMV FORKLIFT TRUCKS SL 22-1200 AV



**ENGINE** Scania DI 9  
Capacity: 20-25 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>Multifleet SCD 30</b>

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

**DIFFERENTIAL**  
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube HS GL-5 80W-140</b>		

**GEARBOX**  
Capacity: 27 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>Gear Oil Alcat 30</b>	

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 10W</b>	<b>Gear Oil Alcat 10W</b>	<b>SP Matic 2032</b>

**HUB REDUCTIONS**  
Capacity: 7 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube HS GL-5 80W-140</b>		

**SMV FORKLIFT TRUCKS SL 22-1200 AV****HYDRAULIC SYSTEM**

Capacity: 243 liter (wheelbase: 4000 mm), Capacity: 293 liter (wheelbase: 4250 mm)

We are unable to give a standard recommendation for this component. Please contact our service department.

**GREASE POINTS/NIPPLES**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2****COOLING SYSTEM**

Capacity: 50 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*