SVEDALA DEMAG TRACKED PAVERS DF45C TYPE 35 (2007 AND AFTER)



| ENGINE Deutz D m2011 L03i | | | | |
|----------------------------|--------------------------|-------------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | Armado Synth LSP Ultra 10W-40 | | |

Check every 10 hours, change every 1000 hours/ 12 months

| PUMP REDUCTION UNIT Capacity: 1,7 liter | | |
|--------------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 10 hours, change every 1500 hours

| HYDRAULIC SYSTEM Capacity: 70 liter (Hydraulic tank) | | | | |
|----------------------------------------------------------|--|---------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | | |
| Perlus H 46 | | | | |
| Check every 10 hours, change every 2000 hours/ 24 months | | | | |
| USE | | CLIMATE | | |
| Biodegradable oil | | Mediterranean | | |
| PRODUCT RECOMMENDATION 1 | | | | |

Perlus Biosynth 46

Check every 10 hours, change every 2000 hours/ 24 months

| GREASE POINTS/NIPPLES | | | |
|--------------------------|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

SVEDALA DEMAG TRACKED PAVERS DF45C TYPE 35 (2007 AND AFTER)



| TRAVEL REDUCTION UNIT Capacity: 0,8 liter | | |
|------------------------------------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Abacot MEP 220 | | |
| Chack avery 250 hours, chapter avery 1000 hours (12 months | | |

Check every 250 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.