## SVETRUCK LIFT TRUCKS 16120-38 VOLVO TAD7



ENGINE Volvo IAD7		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30
Check every 10 hours, change every 2 r	months/ 400 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30

Change every 50 hours

DIFFERENTIAL FRONT		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
Change every 5 months/ 1000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 5 months/ 1000 hours

TRANSMISSION ZF ErgoPower 4/3			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT	

Check every 10 hours, change every 5 months/ 1000 hours

HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
Check eveny 10 hours, change eveny 10 months/ 2000 hours		

Check every 10 hours, change every 10 months/ 2000 hours

## SVETRUCK LIFT TRUCKS 16120-38 VOLVO TAD7



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

COOLING SYSTEM HYDRAULIC BRAKES NO SEPERATE TANK		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 10 hours

COOLING SYSTEM HYDRAULIC BRAKES WITH SEPERATE TANK			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Agrifluid HT-Plus			
Check everv 10 hours			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.