## **SVETRUCK LIFT TRUCKS 37120-54 SCANIA**



ENGINE Scania DC12		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40 Agridiesel CRD+ 15W-40		Kroontrak MTH 10W-30
Check every 10 hours, change every	/ 2 months/ 400 hours	

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30

Change every 50 hours

DIFFERENTIAL FRONT	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
Gearlube HS GL-5 80W-140	

Change every 5 months/ 1000 hours

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 5 months/ 1000 hours

	•	-
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Agrifluid HT
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
TRANSMISSION ZF ErgoPower 4/3		

Check every 10 hours, change every 5 months/ 1000 hours

HYDRAULIC SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46 Perlus H 46		
Check every 10 hours, change ever	ry 10 months/ 2000 hours	·

## **SVETRUCK LIFT TRUCKS 37120-54 SCANIA**



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM ENGINE			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		

COOLING SYSTEM HYDRAULIC BRAKES NO SEPERATE TANK			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus Biosynth 46	Perlus H 46		
Check every 10 hours			

COOLING SYSTEM HYDRAULIC BRAKES WITH SEPERATE TANK		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Check every 10 hours	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.