

SVETRUCK LOG STACKERS TMF TMF

15/11 VOLVO TWD12

**ENGINE** Volvo TWD12

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 2 months/ 400 hours

DIFFERENTIAL FRONT Meritor

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		

Check every 10 hours, change every 5 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 5 months/ 1000 hours

TRANSMISSION POWERSHIFT ZF Ergopower 3WG310 3/3

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 10 hours, change every 10 months/ 2000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SVETRUCK LOG STACKERS TMF TMF

15/11 VOLVO TWD12



COOLING SYSTEM ENGINE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

COOLING SYSTEM HYDRAULIC BRAKES WITH SEPERATE TANK

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

Check every 10 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.