

TADANO FAUN TRUCK CRANES TS-75M-1, CRANE WITHOUT CARRIER



SPEED REDUCER WINCH

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 22	Perlus H 15	Perlus AF 32

Change every 2400 hours/ 24 months

HYDRAULIC SYSTEM

Capacity: 184 liter (System), Capacity: 120 liter (Tank)

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Change every 2000 hours/ 24 months

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 2000 hours/ 24 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 2000 hours/ 24 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		

Change every 2000 hours/ 24 months

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Change every 250 hours/ 3 months

TADANO FAUN TRUCK CRANES TS-75M-1, CRANE WITHOUT CARRIER



USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 250 hours/ 3 months

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 250 hours/ 3 months

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		

Change every 250 hours/ 3 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SWING REDUCTION GEAR

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	Abacot MEP 320

Change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	Abacot MEP 320

Change every 250 hours/ 3 months

TADANO FAUN TRUCK CRANES TS-75M-1, CRANE WITHOUT CARRIER


WINCH REDUCTION GEAR

Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 250 hours/ 3 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.