

TCM FORKLIFT & REACH TRUCKS, PETROL FG30N8 NISSAN H20 (1991-1995)



ENGINE Nissan H20
Capacity: 4,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

HDX 30

Check every 8 hours, change every 200 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Multifleet SHPD 10W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40

Check every 8 hours, change every 200 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

HDX 10W

Check every 8 hours, change every 200 hours

TCM FORKLIFT & REACH TRUCKS, PETROL FG30N8 NISSAN H20 (1991-1995)

**DIFFERENTIAL POWERSHIFT VERSION**

Capacity: 9 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 600 hours, change every 1200 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 1081	SP Gear 5015

Check every 600 hours, change every 1200 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 600 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 1081	SP Gear 5015

*Change every 600 hours***TRANSMISSION Powershift**

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	ATF Dexron II-D	

Check every 200 hours, change every 1200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	ATF Dexron II-D	

Check every 200 hours, change every 600 hours

TCM FORKLIFT & REACH TRUCKS, PETROL FG30N8 NISSAN H20 (1991-1995)



TRANSMISSION MANUAL

Capacity: 11,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 600 hours, change every 1200 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 1081	SP Gear 5015

Check every 600 hours, change every 1200 hours

HYDRAULIC SYSTEM

Capacity: 37 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	Perlus H 32	Perlus H 22

Check every 8 hours, change every 1200 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 8 hours, change every 1200 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

TCM FORKLIFT & REACH TRUCKS, PETROL FG30N8 NISSAN H20 (1991-1995)

**COOLING SYSTEM**

Capacity: 9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 8 hours, change every 24 months/ 600 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.