TCM FORKLIFT & REACH TRUCKS, PETROL FHG30N8



ENGINE		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 30		
Change every 600 hours/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40
Change every 600 hours/ 12 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 600 hours/ 12 months		

DIFFERENTIAL		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1200 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 1081	SP Gear 5015
	'	·

Change every 1200 hours/ 12 months

TRANSMISSION Powershift	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Change every 1200 hours/ 12 months	·

TCM FORKLIFT & REACH TRUCKS, **PETROL FHG30N8**



TRANSMISSION MANUAL		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1200 hours/ 12 mont.	hs	

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1081	SP Gear 5015

Change every 1200 hours/ 12 months

HYDRAULIC SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Perlus H 32	Perlus H 22		

Change every 1200 hours/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 1200 hours/ 12 months		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Lahora Grease	05 MP Calcen Grease FP 2	MP Lithen Grease FP 2

TCM FORKLIFT & REACH TRUCKS, PETROL FHG30N8



FINAL REDUCTION GEAR			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90		
Change every 1200 hours/ 12 month	s		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrifluid HT-Plus	SP Gear 1081	SP Gear 5015	
Change every 1200 hours/ 12 month	s	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.