

TEREX FUCHS TRACKED MATERIAL HANDLERS RHL RHL331E DEUTZ TCD 4.1 L4 TIER 4I (331350/4001 ->)



ENGINE Deutz TCD 4.1 L4
Capacity: 16 liter

USE	CLIMATE
Normal, fuel sulfur level < 0,05 %	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Agridiesel MSP 15W-40

Check every 8 hours, change every 12 months/ 500 hours

HYDRAULIC SYSTEM
Capacity: 900 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus AF 46		

Change every 3000 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Change every 3000 hours/ 12 months

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Change every 3000 hours/ 12 months

GREASE POINTS/NIPPLES CENTRAL LUBRICATING SYSTEM
Capacity: 2 kg

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

GREASE POINTS/NIPPLES SWING RING GEAR
Capacity: 28 kg

We are unable to give a standard recommendation for this component. Please contact our service department.

TEREX FUCHS TRACKED MATERIAL HANDLERS RHL RHL331E DEUTZ TCD 4.1 L4 TIER 4I (331350/4001 ->)

**COOLING SYSTEM**

Capacity: 36 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

TRAVEL REDUCTION UNIT

Capacity: 5 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.