

TEREX FUCHS TRACKED MATERIAL HANDLERS RHL RHL350 039-> (2005 AND AFTER)



ENGINE Deutz BF6M-1013EC
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Kroontrak CVT 10W-40	Agrisynth MSP 10W-40

Check every 8 hours, change every 12 months/ 500 hours

HYDRAULIC SYSTEM
Capacity: 380 liter

USE	CLIMATE
Flexible (max)	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus AF 46		

Change every 3000 hours/ 12 months

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Change every 3000 hours/ 12 months

USE	CLIMATE
Alternative, flexible (max)	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Change every 3000 hours/ 12 months

GREASE POINTS/NIPPLES CENTRAL LUBRICATING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

TEREX FUCHS TRACKED MATERIAL HANDLERS RHL RHL350 039-> (2005 AND AFTER)

**COOLING SYSTEM**

Capacity: 36 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11*Change every 24 months***GRAB GEAR UNIT**

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90**SWING REDUCTION UNIT**

Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90**TRAVEL REDUCTION UNIT**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 1000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.