

TEREX FUCHS STATIONARY MATERIAL HANDLERS AHL AHL820 820010/0001-> (2010 AND AFTER)

**HYDRAULIC SYSTEM**

Capacity: 300 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Perlus AF 46*Change every 3000 hours/ 12 months*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

PRODUCT RECOMMENDATION 2

Perlus H 46*Change every 3000 hours/ 12 months*

| USE | CLIMATE |
|-------------------|---------------|
| Biodegradable oil | Mediterranean |

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Change every 3000 hours/ 12 months***GREASE POINTS/NIPPLES CENTRAL LUBRICATING SYSTEM**

Capacity: 2 kg

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease**GRAB GEAR UNIT**

Capacity: 0,7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 3

Unigear HS GL-3/GL-5 80W-90*Change every 500 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.