TEREX WHEELED EXCAVATORS HML22 131/0512->(2002-2004)



ENGINE Perkins 704-30 Capacity: 8,2 liter			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 40			
Check every 10 hours, change every 500 l	hours/ 12 months		
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 500 hours/ 12 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Armado Synth 5W-30	
Check every 10 hours, change every 500 hours/ 12 months			
USE		CLIMATE	
Initial service		Tropical	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 40			
Change every 100 hours			
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Change every 100 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Armado Synth 5W-30	
01			

Change every 100 hours

TEREX WHEELED EXCAVATORS HML22 131/0512->(2002-2004)



CLIMATE
Moderate

Check every 500 hours, change every 1000 hours/ 12 months

DIFFERENTIAL REAR Capacity: 6,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Charly avery 500 hours, shanes avery 1000 hours (12 months		

Check every 500 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT Capacity: 0,6 liter (each)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
01 1 5001 1 100	

Check every 500 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS REAR Capacity: 0,6 liter (each)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 50 hours, change every 1000 hours/ 12 months

TRANSMISSION Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check even 500 hours, change even 1000 hours (12 months		

Check every 500 hours, change every 1000 hours/ 12 months

TEREX WHEELED EXCAVATORS HML22 131/0512-> (2002-2004)



HYDRAULIC SYSTEM Capacity: 120 liter, Capacity: 104 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Perlus H 68			
Check every 500 hours, change every 1000 hours/ 12 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32	

Check every 500 hours, change every 1000 hours/ 12 months

Perlus Biosynth 46	Perlus Biosynth 32	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Biodegradable oil		Moderate
USE		CLIMATE
check every every every recentered in a mention		

Check every 500 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 24 months

SWING REDUCTION UNIT Capacity: 1,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check avery 500 hours, change avery 1000 hours (12 months		

Check every 500 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.