PRODUCT RECOMMENDATION

TEREX ARTICULATED DUMP TRUCKS 2566C CUMMINS LT10-C250 (1995-1998)

ENGINE Cummins LT10-C250		
USE Normal		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1 **Agridiesel CRD+ 15W-40**	PRODUCT RECOMMENDATION 2 **Dieselfleet CD+ 15W-40**	PRODUCT RECOMMENDATION 3 **Multifleet SHPD 15W-40**
Change every 250 hours/ 1 months		

DIFFERENTIAL AXLE 1		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube LS 80W-90**		
Change every 1000 hours/ 6 months		

DIFFERENTIAL AXLE 2		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube LS 80W-90**		
Change every 1000 hours/ 6 months		

DIFFERENTIAL AXLE 3		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube LS 80W-90**		
Change every 1000 hours/ 6 months		

HUB REDUCTIONS AXLE 1		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Gearlube LS 80W-90**		
Change every 1000 hours/ 6 months		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TEREX ARTICULATED DUMP TRUCKS 2566C CUMMINS LT10-C250 (1995-1998)

HUB REDUCTIONS AXLE 2

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1000 hours/ 6 months		

HUB REDUCTIONS AXLE 3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1000 hours/ 6 months		

TRANSMISSION ZF 6WG200

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 1000 hours/ 6 months		

HYDRAULIC SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367