## TEREX MINI DUMPERS TA10 PERKINS 1104D-44TA TIER 3 (2011-2014)



ENGINE Perkins 1104D-44T Tier III Capacity: 10 liter			
USE		CLIMATE	
Fuel sulfur level >0.2% (2000ppm)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 250 hours			
USE		CLIMATE	
Fuel sulfur level <0,2%		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

<b>DIFFERENTIAL FRONT</b> Dana 112 Capacity: 9,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
	<del></del>	

Check every 50 hours, change every 500 hours

Check every 10 hours, change every 500 hours

<b>DIFFERENTIAL REAR</b> Dana 112 Capacity: 9,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Agrifluid HT-Plus	Agrifluid HT		
Chook ayan, 50 hayra ahanga ayar	500 hours	·	

Check every 50 hours, change every 500 hours

TRANSFERBOX Capacity: 0,45 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 50 hours, change every 500 hours		

## TEREX MINI DUMPERS TA10 PERKINS 1104D-44TA TIER 3 (2011-2014)



<b>TRANSMISSION</b> ITL Synchro Shuttle 4/4 Capacity: 13 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	
Check every 50 hours, change every 500 hours	·

HYDRAULIC SYSTEM
Capacity: 50 liter (Hydraulic tank)

USE
Normal
PRODUCT RECOMMENDATION 1
Perlus H 46

CLIMATE
Moderate

Moderate

Check every 10 hours, change every 500 hours

HYDRAULIC BRAKE SYSTEM Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 10 hours, change every 500	}	

GREASE POINTS/NIPPLES CENTRE PIVOT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Check every 50 hours

GREASE POINTS/NIPPLES OTHE	ERS	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

## **TEREX MINI DUMPERS TA10 PERKINS** 1104D-44TA TIER 3 (2011-2014)



COOLING SYSTEM Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every 12 months		

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.