

TEREX TRACKED EXCAVATORS TC16

0101 -> 0884 (2006-2008)



ENGINE Mitsubishi L3E
Capacity: 3,6 liter (Total), Filter capacity: 0,2 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours/ 6 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE
Initial service

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 20W-50

Change every 100 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40

Change every 100 hours

HYDRAULIC SYSTEM

Capacity: 25 liter (Hydraulic tank), Capacity: 35 liter (Total)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Perlus H 68

Check every 500 hours, change every 1000 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus Biosynth 46

PRODUCT RECOMMENDATION 2
Perlus H 46

PRODUCT RECOMMENDATION 3
Perlus Biosynth 32

Check every 500 hours, change every 1000 hours/ 12 months

TEREX TRACKED EXCAVATORS TC16

0101 -> 0884 (2006-2008)



USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32

Check every 100 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus Biosynth 32	

Check every 500 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service, biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus Biosynth 32	

Check every 100 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 100 hours

TEREX TRACKED EXCAVATORS TC16

0101 -> 0884 (2006-2008)

**COOLING SYSTEM**

Capacity: 4,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 12 months, change every 24 months

SWING REDUCTION UNIT

Capacity: 0,07 liter

USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

TRAVEL REDUCTION UNIT

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 1000 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.