

# TEREX TRACKED EXCAVATORS TC20 0809- > (2008 AND AFTER)



**ENGINE** Mitsubishi L3E  
Capacity: 3,6 liter (Total), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1  
**Multifleet SHPD 20W-50**

*Check every 10 hours, change every 500 hours/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Agrisynth MSP 10W-40**

PRODUCT RECOMMENDATION 3  
**Agridiesel MSP 15W-40**

*Check every 10 hours, change every 500 hours/ 6 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1  
**Multifleet SHPD 20W-50**

*Change every 100 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1  
**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2  
**Agrisynth MSP 10W-40**

PRODUCT RECOMMENDATION 3  
**Agridiesel MSP 15W-40**

*Change every 100 hours*

## HYDRAULIC SYSTEM

Capacity: 25 liter (Hydraulic tank), Capacity: 35 liter (Total)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1  
**Perlus H 68**

*Check every 500 hours, change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1  
**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2  
**Perlus H 46**

PRODUCT RECOMMENDATION 3  
**Perlus Biosynth 32**

*Check every 500 hours, change every 1000 hours/ 12 months*

# TEREX TRACKED EXCAVATORS TC20 0809- > (2008 AND AFTER)



USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Check every 100 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	<b>Perlus Biosynth 32</b>

*Check every 100 hours*

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus Biosynth 32</b>	

*Check every 500 hours, change every 1000 hours/ 12 months*

USE		CLIMATE
Initial service, biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus Biosynth 32</b>	

*Check every 100 hours*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 500 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 100 hours*

# TEREX TRACKED EXCAVATORS TC20 0809- > (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 4,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 12 months, change every 24 months*

**SWING REDUCTION UNIT**

Capacity: 0,1 liter

USE		CLIMATE
Filled for life		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

**TRAVEL REDUCTION UNIT**

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Check every 500 hours, change every 1000 hours/ 12 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 100 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*