## TEREX TRACKED EXCAVATORS TC35 0101 -> 0556 (2006-2008)



JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every 5	00 hours/ 6 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Check every 10 hours, change every 5	00 hours/ 6 months	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Change every 100 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40
Change every 100 hours		
HYDRAULIC SYSTEM		
Capacity: 72 liter (Hydraulic tank), Cap	acity: 85 liter (Total)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		

PRODUCT RECOMMENDATION 2

Perlus H 46

Check every 500 hours, change every 1000 hours/ 12 months

USE

Normal

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

CLIMATE

Moderate

PRODUCT RECOMMENDATION 3

Perlus Biosynth 32

## TEREX TRACKED EXCAVATORS TC35 0101 -> 0556 (2006-2008)



USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 100 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32
Check every 100 hours		
USE		CLIMATE
use Biodegradable oil		climate Moderate
***	PRODUCT RECOMMENDATION 2	
Biodegradable oil	PRODUCT RECOMMENDATION 2 Perlus Biosynth 32	
Biodegradable oil PRODUCT RECOMMENDATION 1	Perlus Biosynth 32	
Biodegradable oil PRODUCT RECOMMENDATION 1 Perlus Biosynth 46	Perlus Biosynth 32	
Biodegradable oil  PRODUCT RECOMMENDATION 1  Perlus Biosynth 46  Check every 500 hours, change every 100	Perlus Biosynth 32	Moderate
Biodegradable oil  PRODUCT RECOMMENDATION 1  Perlus Biosynth 46  Check every 500 hours, change every 100  use	Perlus Biosynth 32	Moderate
Biodegradable oil  PRODUCT RECOMMENDATION 1  Perlus Biosynth 46  Check every 500 hours, change every 100  USE  Initial service, biodegradable oil	Perlus Biosynth 32 00 hours/ 12 months	Moderate

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 500 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Gearlube LS 80W-90

Change every 100 hours

## TEREX TRACKED EXCAVATORS TC35 0101 -> 0556 (2006-2008)



COOLING SYSTEM Capacity: 5,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 12 months, change every 24 months

TRAVEL REDUCTION UNIT Capacity: 0,6 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gearlube LS 80W-90				
Check every 500 hours, change every 1000 hours/ 12 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V. Postbus 149 7600 AC Almelo