ENGINE Deutz TD 2011 L04W

TEREX TRACKED EXCAVATORS TC75 + DPF 1040->1710 (2008-2012)



USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrisynth LSP 10W-40		
Check every 10 hours, change ever	y 500 hours/ 12 months	
LIVER ALL IO OVETEM		
HYDRAULIC SYSTEM Capacity: 110 liter (Hydraulic tank),	Capacity: 140 liter (Total)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 500 hours, change eve	ery 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus Biosynth 46	Perlus H 46	Perlus Biosynth 32
Check every 500 hours, change eve	ery 1000 hours	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Check every 100 hours		
USE		CLIMATE

Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus Biosynth 32	

PRODUCT RECOMMENDATION 2

Perlus H 46

Check every 500 hours, change every 1000 hours

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

Check every 100 hours

PRODUCT RECOMMENDATION 3

Perlus Biosynth 32

TEREX TRACKED EXCAVATORS TC75 + DPF 1040->1710 (2008-2012)



use Initial service, biodegradable oil		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus Biosynth 32	
01 1 1001		

Check every 100 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 500 hours		·
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 100 hours		·

COOLING SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

Check every 10 hours, change every 24 months

TRAVEL REDUCTION UNIT Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 100)0 hours/ 12 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 100 hours		
	A	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

TEREX TRACKED EXCAVATORS TC75 + DPF 1040->1710 (2008-2012)



information contained herein is subject to changes without notification.