

# TEREX RIGID DUMP TRUCKS TR35 (TILL 2002)



<b>ENGINE</b> Cummins M11-C350		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>
<i>Change every 250 hours/ 1 months</i>		

<b>DIFFERENTIAL REAR + HUB REDUCTIONS</b>		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		
<i>Change every 1000 hours</i>		

**POWER TAKE-OFF ENGINE**  
 We are unable to give a standard recommendation for this component. Please contact our service department.

**TRANSMISSION** Allison CLBT-754 Automatic  
 We are unable to give a standard recommendation for this component. Please contact our service department.

<b>GREASE POINTS/NIPPLES</b>		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

<b>MAIN HYDRAULIC SYSTEM</b>		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		
<i>Change every 1000 hours</i>		

# TEREX RIGID DUMP TRUCKS TR35 (TILL 2002)



## STEERING HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		

Change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

Change every 1000 hours

## TRACTION BIAS DIFFERENTIAL

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

## WHEEL BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*