

TEREX TELEHANDLERS SS-1048C (2005 AND AFTER)



ENGINE John Deere 4045 T
Capacity: 12,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	AgriDiesel MSP 15W-40

Check every 10 hours, change every 500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	AgriDiesel MSP 15W-40

Check every 10 hours, change every 100 hours

DIFFERENTIAL FRONT
Capacity: 14,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 50 hours, change every 750 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 50 hours, change every 100 hours

DIFFERENTIAL REAR
Capacity: 14,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 50 hours, change every 750 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 50 hours, change every 100 hours

TEREX TELEHANDLERS SS-1048C (2005 AND AFTER)



HUB REDUCTIONS FRONT

Capacity: 1,6 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 750 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 100 hours*

HUB REDUCTIONS REAR

Capacity: 1,6 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 750 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 100 hours*

TRANSMISSION Powershift

Capacity: 18,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM

Capacity: 197 liter

USE	CLIMATE
Flexible, fluid analysis	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus AF 46*Check every 10 hours*

TEREX TELEHANDLERS SS-1048C (2005 AND AFTER)



COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.