

TEREX TELEHANDLERS TEREXLIFT TX 51-19S

**ENGINE**

Capacity: 8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 15W-40***Check every 10 hours, change every 250 hours***DIFFERENTIAL FRONT**

Capacity: 5,9 liter (+ Transferbox)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Change every 1000 hours***DIFFERENTIAL REAR**

Capacity: 5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Change every 1000 hours***HUB REDUCTIONS FRONT**

Capacity: 1,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Change every 1000 hours***HUB REDUCTIONS REAR**

Capacity: 0,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube LS 80W-90***Change every 1000 hours*

TEREX TELEHANDLERS TEREXLIFT TX 51-19S



TRANSFERBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
<i>Change every 1000 hours</i>		

HYDRAULIC SYSTEM

Capacity: 76 liter

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Perlus H 68		
<i>Check every 10 hours, change every 1000 hours</i>		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
<i>Check every 10 hours, change every 1000 hours</i>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 22		
<i>Check every 10 hours, change every 1000 hours</i>		

HYDRAULIC BRAKE SYSTEM

Capacity: 0,5 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	
<i>Change every 1000 hours</i>		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

TEREX TELEHANDLERS TEREXLIFT TX 51-19S


COOLING SYSTEM

Capacity: 25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.