

TEREX TELEHANDLERS TH-528C (2004 AND AFTER)



ENGINE Cummins
Capacity: 8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-------------------------------|
| Kroontrak CVT 10W-40 | Agrisynth MSP 10W-40 | Agri diesel MSP 15W-40 |

Check every 10 hours, change every 500 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-------------------------------|
| Kroontrak CVT 10W-40 | Agrisynth MSP 10W-40 | Agri diesel MSP 15W-40 |

Check every 10 hours, change every 100 hours

DIFFERENTIAL FRONT
Capacity: 8,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 50 hours, change every 750 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 50 hours, change every 100 hours

DIFFERENTIAL REAR
Capacity: 8,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 50 hours, change every 750 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Gearlube LS 80W-90 | | |

Check every 50 hours, change every 100 hours

TEREX TELEHANDLERS TH-528C (2004 AND AFTER)



HUB REDUCTIONS FRONT

Capacity: 0,9 liter (each)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 750 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 100 hours*

HUB REDUCTIONS REAR

Capacity: 0,9 liter (each)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 750 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 50 hours, change every 100 hours*

TRANSMISSION

Capacity: 12,9 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 3

ATF Dexron II-D*Check every 10 hours, change every 500 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 3

ATF Dexron II-D*Check every 10 hours, change every 100 hours*

TEREX TELEHANDLERS TH-528C (2004 AND AFTER)



HYDRAULIC SYSTEM

Capacity: 193 liter, Capacity: 136 liter (Hydraulic tank)

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Flexible, fluid analysis | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Perlus H 46 | Perlus AF 46 | |

Check every 10 hours

COOLING SYSTEM

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.