PRODUCT RECOMMENDATION

TOUCAN MAST STYLE BOOM LIFTS V2642E

HYDRAULIC SYSTEM
Capacity: 30 liter (System), Capacity: 22 liter (Tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Check every 8 hours, change every 24 months/ 1000 hours

STEERING BAR
Capacity: 1,5 liter (System), Capacity: 1 liter (Tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Check every 8 hours, change every 24 months/ 1000 hours

SWING BEARING RACE

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 250 hours

SWING BEARING TEETH

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL HUB BEARING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 250 hours

LIFTING CHAINS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Change every 125 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TOUCAN MAST STYLE BOOM LIFTS V2642E

MAST PROFILES / SHELF PROFILES		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Labora Grease**	PRODUCT RECOMMENDATION 2 **Q5 MP Calcep Grease EP 2**	PRODUCT RECOMMENDATION 3 **MP Lithep Grease EP 2**
Change every 125 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367