Check every 8 hours, change every 6 weeks/ 250 hours

TOYOTA FORKLIFT TRUCKS, DIESEL 02-8FDF25 (2007-2012)



ENGINE Toyota 1DZ-III Capacity: 7,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet LSP Ultra 10W-30
Check every 8 hours, change every 3 months/ 500 hours		
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 8 hours, change every 6 wee	ks/ 250 hours	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40

DIFFERENTIAL Capacity: 6,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90
Check every 6 months/ 250 hours.	change every 12 months/ 2000 hours	-

TRANSMISSION + TORQUE CONVERTER Capacity: 6-10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 40 hours, change every 12 months/ 2000 hours		

TOYOTA FORKLIFT TRUCKS, DIESEL 02-8FDF25 (2007-2012)



HYDRAULIC SYSTEM Capacity: 33 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Check every 8 hours, change every 6 months/ 1000 hours		

HYDRAULIC BRAKE SYSTEM Capacity: 0,2 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 8 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Change every 40 hours/ 1 each race	·

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 1000 hours/ 6 months	<u> </u>	

Change every 1000 hours/ 6 months

COOLING SYSTEM Capacity: 7,91 liter, Capacity: 0,47 liter (Reservoir)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.