

# TOYOTA FORKLIFT TRUCKS, DIESEL 50-8FD30 TOYOTA 3Z (2007 AND AFTER)



**ENGINE** Toyota 3Z  
Capacity: 9 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Dieselfleet LSP Ultra 10W-30</b>

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Check every 10 hours, change every 250 hours*

**DIFFERENTIAL**  
Capacity: 8,2 liter, Capacity: 8,4 liter (Wet brake models)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-4 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 250 hours, change every 2000 hours/ 12 months*

**TRANSMISSION**  
Capacity: 6 liter, Capacity: 10 liter (2 stator T/C)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

*Check every 40 hours, change every 6 months/ 1000 hours*

# TOYOTA FORKLIFT TRUCKS, DIESEL 50-8FD30 TOYOTA 3Z (2007 AND AFTER)



## HYDRAULIC SYSTEM

Capacity: 34 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

Check every 40 hours, change every 6 months/ 1000 hours

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,2 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

Check every 8 hours, change every 6 months/ 1000 hours

## WET BRAKE SYSTEM

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

Check every 8 hours, change every 6 months/ 1000 hours

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

Change every 40 hours/ 1 each race

## COOLING SYSTEM

Capacity: 7,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.