

# TOYOTA FORKLIFT TRUCKS, LPG/PETROL

## 02-8FGF30 (2007-2012)



**ENGINE** Toyota 4Y  
Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

*Check every 8 hours, change every 3 months/ 500 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 2

**Synfleet SHPD 10W-40**

*Check every 8 hours, change every 6 weeks/ 250 hours*

**DIFFERENTIAL**  
Capacity: 8,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Unigear HS GL-3/GL-5 80W-90**

*Check every 6 months/ 250 hours, change every 12 months/ 2000 hours*

**TRANSMISSION + TORQUE CONVERTER**  
Capacity: 6-10 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

*Check every 40 hours, change every 12 months/ 2000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 34 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32**

*Check every 8 hours, change every 6 months/ 1000 hours*

# TOYOTA FORKLIFT TRUCKS, LPG/PETROL

## 02-8FGF30 (2007-2012)



### HYDRAULIC BRAKE SYSTEM

Capacity: 0,2 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 8 hours, change every 6 months/ 1000 hours*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

*Change every 40 hours/ 1 each race*

### GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

*Change every 1000 hours/ 6 months*

### COOLING SYSTEM

Capacity: 9,28 liter, Capacity: 0,47 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*