## TOYOTA FORKLIFT TRUCKS, LPG/PETROL 50-8FG35 (2007 AND AFTER)



ENGINE Toyota 4Y Capacity: 4 liter		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Check every 10 hours, change every 500 h	nours	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	Synfleet SHPD 10W-40	

Check every 10 hours, change every 250 hours

DIFFERENTIAL Capacity: 8,2-8,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 250 hours, change every 2000 hours/ 12 months

TRANSMISSION Capacity: 6 liter, Capacity: 10 liter (2 stator	T/C)
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
	·

Check every 40 hours, change every 6 months/ 1000 hours

HYDRAULIC SYSTEM Capacity: 34 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Check every 40 hours, change every 6 mo	nths/ 1000 hours	

## TOYOTA FORKLIFT TRUCKS, LPG/PETROL 50-8FG35 (2007 AND AFTER)



HYDRAULIC BRAKE SYSTEM Capacity: 0,2 liter (Reservoir)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 8 hours, change every 6 months/ 1000 hours

WET BRAKE SYSTEM Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus

Check every 8 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

Change every 40 hours/ 1 each race

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Coolant -26		
		PRODUCT RECOMMENDATION 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.