## TOYOTA FORKLIFT TRUCKS, LPG/PETROL 5FG50 TOYOTA 1FZ-E (2007-2015)



<b>ENGINE</b> Toyota 1FZ-E Capacity: 9,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Asyntho 5W-30	

Check every 8 hours, change every 6 weeks/ 250 hours

<b>DIFFERENTIAL</b> Capacity: 6,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90 Gearlube GL-5 80W-90		Unigear HS GL-3/GL-5 80W-90
Check every 6 weeks/ 250 hours, ci	hange every 6 months/ 1000 hours	<u> </u>

PLANETARY GEARS
Capacity: 1,5 liter (each)

USE

Normal

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W-90

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Unigear HS GL-3/GL-5 80W-90

Check every 6 weeks/250 hours, change every 6 months/ 1000 hours

TRANSMISSION + TORQUE CONVERTER Capacity: 18 liter				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
ATF Dexron II-D				
Check every 40 hours, change every 6 months/ 1000 hours				

HYDRAULIC SYSTEM Capacity: 90-100 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
Check every 8 hours, change every 6	months/ 1000 hours	

## TOYOTA FORKLIFT TRUCKS, LPG/PETROL 5FG50 TOYOTA 1FZ-E (2007-2015)



GREASE POINTS/NIPPLES GENERAL			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Change every 40 hours/1 each rac	0		

Change	everv	40	hours/	1	each r	ace
--------	-------	----	--------	---	--------	-----

WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 2000 hours/ 12 mon	ths	1

## **COOLING SYSTEM**

Capacity: 13 liter, Capacity: 1,1 liter (Reservoir)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.