

TOYOTA FORKLIFT TRUCKS, LPG/PETROL

6FG10 TOYOTA 5K (1994-2000)



ENGINE Toyota 5K
Capacity: 4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

HDX 20W-50

PRODUCT RECOMMENDATION 2

HDX 30

Check every 8 hours, change every 1 months/ 170 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

Check every 8 hours, change every 1 months/ 170 hours

DIFFERENTIAL

Capacity: 5,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 3

Unigear HS GL-3/GL-5 80W-90

Check every 1 months/ 170 hours, change every 12 months/ 2000 hours

TRANSMISSION + TORQUE CONVERTER

Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 3

Unigear HS GL-3/GL-5 80W-90

Check every 1 months/ 170 hours, change every 12 months/ 2000 hours

HYDRAULIC SYSTEM

Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32

Check every 8 hours, change every 6 months/ 1000 hours

TOYOTA FORKLIFT TRUCKS, LPG/PETROL

6FG10 TOYOTA 5K (1994-2000)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 8 hours, change every 6 months/ 1000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 7,1 liter, Capacity: 1,1 liter (Reservoir)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.