VALMET (KOMATSU FOREST) WHEELED HARVESTERS 931.1



ENGINE Agco Sisu 74 AWI Capacity: 24 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40
Change every 500 hours/ 12 month	S	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40
01 (00)	1	1

Change every 100 hours

DIFFERENTIAL BOGIE AXLE Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 km, change every 2000 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		
Check over 500 km, change over 2000 hours		

Check every 500 km, change every 2000 hours

DIFFERENTIAL SINGLE AXLE Capacity: 32 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
<u> </u>	

Check every 500 hours, change every 1500 hours

VALMET (KOMATSU FOREST) WHEELED HARVESTERS 931.1



PLANETARY REDUCTION UNIT SINGLE AXLE			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			

Check every 500 hours, change every 1500 hours

TRANSFERBOX Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 300 hours, change every 1500 hours

BOGIE CASING Capacity: 55 liter (Complete change), Capacity: 5 liter (Partial change)			
USE		CLIMATE	
Partial change		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Check every 500 hours, change every 1000 hours			
USE		CLIMATE	
Complete change		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Check every 500 km, change every 2000 hours			

VALMET (KOMATSU FOREST) WHEELED HARVESTERS 931.1



HYDRAULIC SYSTEM Capacity: 220 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46
Change every 2000 hours/ 12 months		·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 32	Perlus H 22	Perlus AF 32
Change every 2000 hours/ 12 months		·
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 2000 hours/ 12 months	•	·

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -33 MPG		
Change avery 24 months	·	•

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.