VERMEER TRACKED TRENCHERS T1555



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Change every 50 hours

TRANSFERBOX			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		

Change every 50 hours

HYDRAULIC SYSTEM HYDROSTATIC DRIVE				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Perlus H 68				
Change every 1000 hours				
USE	CLIMATE			
Initial service	Moderate			
PRODUCT RECOMMENDATION 1				
Perlus H 68				
Change every 100 hours				

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
HT Q9 High Grade Grease	

VERMEER TRACKED TRENCHERS T1555



Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Moderate
USE		CLIMATE
TRACK DRIVE GEARBOX		

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.