

# VERMEER DIRECTIONAL DRILLING SYSTEMS D50X100A



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	
<i>Change every 50 hours</i>		

HYDRAULIC SYSTEM HYDROSTATIC DRIVE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		
<i>Change every 1000 hours</i>		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		
<i>Change every 100 hours</i>		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>HT Q9 High Grade Grease</b>		

TRACK DRIVE GEARBOX		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	
<i>Change every 50 hours</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.