

# VOLVO BACKHOE LOADERS BL BL61B

## (2011-2015)



**ENGINE** Volvo D5D CAE3 Stage IIIA/Tier 3  
Capacity: 14-15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra FE 5W-30**

PRODUCT RECOMMENDATION 2

**Agrisynth LSP Ultra 10W-40**

PRODUCT RECOMMENDATION 3

**Agrisynth LSP 10W-40**

*Check every 8 hours, change every 500 hours*

**DIFFERENTIAL FRONT**

Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT**

*Change every 1000 hours*

**DIFFERENTIAL REAR**

Capacity: 14,5 liter (+ hub reductions)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT**

*Change every 1000 hours*

**HUB REDUCTIONS FRONT**

Capacity: 0,8 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT**

*Change every 1000 hours*

**HUB REDUCTIONS REAR**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Agrifluid HT**

*Change every 1000 hours*

# VOLVO BACKHOE LOADERS BL BL61B

## (2011-2015)



**TRANSMISSION** Powershift 4/4  
Capacity: 14-16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 2000 hours*

**TRANSMISSION** PowerShuttle 4/4  
Capacity: 14-16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>	

*Change every 2000 hours*

**HYDRAULIC SYSTEM**  
Capacity: 39 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Perlus H 68</b>		

*Check every 8 hours, change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus H 32</b>	

*Check every 8 hours, change every 1000 hours*

**COOLING SYSTEM**  
Capacity: 22 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Check every 8 hours, change every 6000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*