

# VOLVO WHEELED LOADERS L L50G LOW SPEED STAGE IIIB/TIER 4I (2012-2015)



**ENGINE** Volvo D4H Tier 4i  
Capacity: 11,5 liter

USE	CLIMATE
Fuel sulfur level <15 ppm	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>

*Check every 8 hours, change every 12 months/ 500 hours*

USE	CLIMATE
Alternative, fuel sulfur level < 15 ppm	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra FE 5W-30</b>	<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth MSP 10W-40</b>

*Check every 8 hours, change every 12 months/ 250 hours*

**DIFFERENTIAL FRONT**  
Capacity: 17,5 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid Synth XHP Ultra</b>		

*Change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 1000 hours/ 12 months*

**DIFFERENTIAL REAR**  
Capacity: 17,5 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid Synth XHP Ultra</b>		

*Change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		

*Change every 1000 hours/ 12 months*

# VOLVO WHEELED LOADERS L L50G LOW SPEED STAGE IIIB/TIER 4I (2012-2015)



## TRANSFERBOX

Capacity: 1,2 liter

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra***Change every 1000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 1000 hours/ 12 months*

## HYDRAULIC SYSTEM

Capacity: 95 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus H 46**

PRODUCT RECOMMENDATION 2

**Perlus H 68***Change every 1500 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 1500 hours/ 12 months*

USE	CLIMATE
Biodegradable oil	Mediterranean

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46***Change every 1500 hours/ 12 months*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

# VOLVO WHEELED LOADERS L L50G LOW SPEED STAGE IIIB/TIER 4I (2012-2015)

**COOLING SYSTEM**

Capacity: 20 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12***Change every 48 months/ 6000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*