VOLVO WHEELED LOADERS L L70F (2007-2011)



ENGINE Volvo D6E LBE3 Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Change every 600 hours

DIFFERENTIAL FRONT Capacity: 35 liter		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid Synth XHP Ultra		
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours		

DIFFERENTIAL REAR Capacity: 27 liter	
USE	CLIMATE
Extended	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid Synth XHP Ultra	
Change every 2000 hours	·

Change every 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours		

KROON-OIL B.V. Postbus 149 7600 AC Almelo

VOLVO WHEELED LOADERS L L70F (2007-2011)



HUB REDUCTIONS FRONT		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid Synth XHP Ultra		
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours		

HUB REDUCTIONS REAR		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid Synth XHP Ultra		
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours		

TRANSMISSION Volvo HTE 120 Capacity: 20 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Change every 2000 hours	1	1	

HYDRAULIC SYSTEM Capacity: 90 liter (Tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	
Change every 4000 hours	'	

VOLVO WHEELED LOADERS L L70F (2007-2011)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

COOLING SYSTEM Capacity: 30 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change every 48 months/ 6000 ho	urs	-

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.