

# VOLVO TRACKED EXCAVATORS EC EC240 LC (1999-2001)



**ENGINE** Cummins B8.3C  
Capacity: 25,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40**

*Change every 250 hours/ 12 months*

## HYDRAULIC SYSTEM

Capacity: 190 liter (Hydraulic tank), Capacity: 320 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus H 46**

*Change every 2000 hours/ 12 months*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

## COOLING SYSTEM

Capacity: 26,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

*Change every 2000 hours*

## CARRIER ROLLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

# VOLVO TRACKED EXCAVATORS EC EC240 LC (1999-2001)



## SWING REDUCTION UNIT

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

Change every 12 months/ 4000 hours

## TRACK IDLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

## TRACK ROLLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

## TRAVEL REDUCTION UNIT

Capacity: 5,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

Change every 12 months/ 4000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.