# VOLVO TRACKED EXCAVATORS EC EC55C
## (2008-2018)

**ENGINE** Volvo D3.1D EPA3 / EU Stage IIIA
Capacity: 11,5 liter

| USE | | | CLIMATE | |
|-----|-----|-----|---------|-----|
| Normal | | | Moderate | |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | | **PRODUCT RECOMMENDATION 3** | |
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | | Agridiesel CRD+ 15W-40 | |

*Check every 8 hours, change every 500 hours*

**HYDRAULIC SYSTEM**
Capacity: 84 liter

| USE | | | CLIMATE | |
|-----|-----|-----|---------|-----|
| Normal | | | Mediterranean | |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | | **PRODUCT RECOMMENDATION 3** | |
| Perlus Biosynth 46 | Perlus H 46 | | Perlus H 68 | |

*Change every 1000 hours*

| USE | | | CLIMATE | |
|-----|-----|-----|---------|-----|
| Normal | | | Moderate | |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | | | |
| Perlus Biosynth 32 | Perlus H 32 | | | |

*Change every 1000 hours*

**GREASE POINTS/NIPPLES**

| USE | | | CLIMATE | |
|-----|-----|-----|---------|-----|
| Normal | | | Moderate | |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | | **PRODUCT RECOMMENDATION 3** | |
| Labora Grease | Q5 MP Calcep Grease EP 2 | | MP Lithep Grease EP 2 | |

**COOLING SYSTEM**
Capacity: 16 liter

| USE | | | CLIMATE | |
|-----|-----|-----|---------|-----|
| Normal | | | Moderate | |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | | | |
| Coolant SP 15+ | Coolant SP 12 | | | |

*Change every 2000 hours*

# VOLVO TRACKED EXCAVATORS EC EC55C
## (2008-2018)

| TRAVEL REDUCTION UNIT | |
|---|---|
| **Capacity: 1,3 liter** | |
| **USE** | **CLIMATE** |
| Normal | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** |
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |

*Change every 1000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*