WACKER NEUSON ASPHALT COMPACTORS RD RD10 (2002 AND AFTER)



ENGINE Hatz 1D81Z Capacity: 1,8 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Check every 10 hours, change every 250 l	hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 250 l	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40
Check every 10 hours, change every 250 l	hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 250 l	hours	

WACKER NEUSON ASPHALT COMPACTORS RD RD10 (2002 AND AFTER)



HYDRAULIC SYSTEM Capacity: 25 liter				
USE		CLIMATE		
Normal		Tropical		
PRODUCT RECOMMENDATION 1				
Perlus H 68				
Check every 10 hours, change every 1200	hours			
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Perlus H 46				
Check every 10 hours, change every 1200 hours				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Perlus H 22				

Check every 10 hours, change every 1200 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

EXCITER Capacity: 0,13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP 100		
Check every 250 hours, change every 500 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.