

WACKER NEUSON ASPHALT COMPACTORS RD RD12 (2011 AND AFTER)



ENGINE Wacker Neuson WM650
Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Asyntho 5W-30	Synfleet SHPD 10W-40

Change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Asyntho 5W-30	Synfleet SHPD 10W-40

Change every 20 hours

HYDRAULIC SYSTEM
Capacity: 20,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 10 hours, change every 1200 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Check every 100 hours

GREASE POINTS/NIPPLES DRUM DRIVE BEARING REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Check every 100 hours

WACKER NEUSON ASPHALT COMPACTORS RD RD12 (2011 AND AFTER)

**EXCITER****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**HT Q9 High Grade Grease****PRODUCT RECOMMENDATION 2****Labora Grease***Check every 100 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.