

# WACKER NEUSON DUMPERS 10001

## PERKINS 1104C-44T (AB91013F ->)



**ENGINE** Perkins 1104C-44T  
Capacity: 10 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40***Change every 250 hours/ 6 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 250 hours/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra FE 5W-30**

PRODUCT RECOMMENDATION 2

**Agrisynth LSP 10W-40**

PRODUCT RECOMMENDATION 3

**Kroontrak CVT 10W-40***Change every 250 hours/ 6 months*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Change every 250 hours/ 6 months*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 40***Change every 50 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra FE 5W-30**

PRODUCT RECOMMENDATION 2

**Agrisynth LSP 10W-40**

PRODUCT RECOMMENDATION 3

**Kroontrak CVT 10W-40***Change every 50 hours*

# WACKER NEUSON DUMPERS 10001

## PERKINS 1104C-44T (AB91013F ->)



USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		
<i>Change every 50 hours</i>		

DIFFERENTIAL FRONT		
Capacity: 4,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		
<i>Change every 1000 hours/ 12 months</i>		

DIFFERENTIAL REAR		
Capacity: 4,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		
<i>Change every 1000 hours/ 12 months</i>		

TRANSFERBOX		
Capacity: 0,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube LS 80W-90</b>		
<i>Change every 1000 hours/ 12 months</i>		



# WACKER NEUSON DUMPERS 10001

## PERKINS 1104C-44T (AB91013F ->)



### HYDRAULIC SYSTEM

Capacity: 70 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	

*Change every 500 hours*

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		

*Change every 500 hours*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>MoS2 Grease EP 2</b>		

### COOLING SYSTEM

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Change every 1000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.