## WACKER NEUSON DUMPERS 5001 YANMAR 4TNE84T (<- AC45000D)



<b>ENGINE</b> Yanmar 4TNE84T Capacity: 8,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Change every 50 hours	1	I

Change every 50 hours

DIFFERENTIAL FRONT			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Gearlube LS 80W-90			
Change every 1000 hours	· ·		

DIFFERENTIAL REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 1000 hours	· ·

## WACKER NEUSON DUMPERS 5001 YANMAR 4TNE84T (<- AC45000D)



HYDRAULIC SYSTEM Capacity: 48 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Perlus Biosynth 46	Perlus H 46			
Change every 18 months/ 1000 hours				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Perlus Biosynth 46	Perlus H 46			
Change avery 500 hours (12 months				

Change every 500 hours/ 12 months

GREASE POINTS/NIPPLES			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
MoS2 Grease EP 2			
Change every 250 hours/ 6 months	·		

COOLING SYSTEM Capacity: 10 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 1000 hours/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.