

# WACKER NEUSON TRACKED EXCAVATORS 1902RD YANMAR 3TNE74- NSR (TILL 2000)



**ENGINE** Yanmar 3TNE74-NSR  
Capacity: 2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 10W-40**

## HYDRAULIC SYSTEM

Capacity: 31 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

PRODUCT RECOMMENDATION 2

**Perlus H 46**

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46**

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## COOLING SYSTEM

Capacity: 3,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26**

## TRAVEL REDUCTION UNIT

Capacity: 0,5 liter (each)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or*

# **WACKER NEUSON TRACKED EXCAVATORS 1902RD YANMAR 3TNE74- NSR (TILL 2000)**



*inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*