WACKER NEUSON TRACKED EXCAVATORS 2503 KUBOTA D1403-B(E) (AB00001-> AC09999)



IICE .		CLIMATE
use Normal		climate Tropical
PRODUCT RECOMMENDATION 1		1, 11
Multifleet SCD 40		
Change every 250 hours	<u>'</u>	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 250 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 3 Kroontrak CVT 10W-40
	Agrisyritii LSF 10VV-40	RIOOHIIAK CVI 10W-40
Change every 250 hours		
use Normal		CLIMATE Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours		
USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Change every 50 hours		
		CLIMATE
		Mediterranean
Initial service PRODUCT RECOMMENDATION 1		
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours		
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE		Mediterranean
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE Initial service PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Mediterranean

WACKER NEUSON TRACKED EXCAVATORS 2503 KUBOTA D1403-B(E) (AB00001-> AC09999)



use Initial service	CLIMATE Cold
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	

HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
COOLING SYSTEM Capacity: 2,7 liter (Engine only)		

TRAVEL REDUCTION UNIT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.